



CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Cleeve Road, Leatherhead, Surrey KT22 7NF England
Telephone: +44 (0) 1372 226 111
Fax: +44 (0) 1372 226 116
www.vca.gov.uk
Registered Number: 385209
England Limited Liability.



Certificate serial number: 6127

NOT TRANSFERABLE

Application No.: 8380

Issue number and date: 02 27/11/2014

This issue cancels all previous issues of this certificate

Issued to: RAMSDEN & WHALE LTD

Packaging type: 1A1 Description:

Harrold Street
Great Bridge
Tipton
West Midlands
DY4 OJF

Drum, steel, non-removable head

Stainless: No Metal thickness Body: 0.80 mm Base: 0.90 mm Head: 0.90 mm Tare: 15.3 kg Capacity: 210 litres
Tinplated: No Diameter: 583 mm Height: 878 mm Rolling hoop(s): Yes Handle:

CLOSURES: No in Head: 2 No in Body: 0 Closures may be any of the following:

Mild steel	Mild steel
Size: 2"	Size: 3/4"
Type:	Type:
Steel screwbung	Steel screwbung
Maker:	Maker:
Technocraft Int.	Technocraft Int.
Tri-Sure	Tri-Sure
Overcap: <input type="checkbox"/>	Overcap: <input type="checkbox"/>
Washer/wad and Closure Torque	Washer/wad and Closure Torque
Nitrile 20 Nm	Nitrile 10 Nm
Nm	Nm

Special Notes:

Drum can include optional 'W' rolling hoop in place of a single pushed out rolling hoop.

There may be additional options please see full report(s)

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:

The packaging is approved, as provided in the relevant transport rule, to contain liquids of:

DROP HEIGHT (m)	1.9	packing group	density (d)	gross mass (kg)
LEAKPROOFNESS (kPa)	30	I	-	-
STACKED AT 3m with RD (d)	1.9	II	1.9	416
INTERNAL PRESSURE (kPa)	250	III	1.9	416

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

1A1/Y1.9/250/**/GB/6127

** To be replaced by the last two digits of the year of manufacture

Revalidation due by: 31/12/ 2019

For further details see www.vca.gov.uk

Signed:

Keith F.B. White

Keith F B White, Principal Consultant VCA DGO