







VCA Dangerous Goods Office Wesley House Bull Hill, Leatherhead Surrey, KT22 7AH, UK T+44 (0)1372 226110 E dgenguiries@vca.gov.uk www.vehicle-certification-agency.gov.uk

PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number:

3568

NOT TRANSFERABLE

Application No.:

3528

Issue number and date:

03

This issue cancels all previous issues of this certificate

Issued to:

Packaging type:

1A1 Description:

RAMSDEN & WHALE LTD

14/06/2023

Drum, steel, non-removable head

Harrold Street Great Bridge Tipton

West Midlands DY4 OJF

Stainless:

No Metal thickness Body:

1.00 mm

Base:

1.00 mm Head:

Tare: 17.2 kg 1.00 mm

Tinplated:

No Diameter:

585 mm

Height:

885 mm

Rolling hoop(s):

Yes Handle:

Capacity: 210 litres

CLOSURES: No in Head: 2 No in Body: 0

| Steel | | Steel | | |
|----------------------------------|-------|----------------------------------|-------|--|
| Size: 2" | | Size: 3/4 | ." | |
| Type: | | Type: | | |
| Screwbung | | Screwbung | | |
| Maker: | | Maker: | | |
| Tri-Sure | | Tri-Sure | | |
| Pro-Seal | | Hong Leong | | |
| Technocraft | | Technocraft | | |
| Overcap: | | Overcap: | | |
| Washer/wad and Closure Torque | | Washer/wad and Closure Torque | | |
| Rubber | 30 Nm | Rubber | 10 Nm | |
| Plastics | 40 Nm | Plastics | 15 Nm | |

Special Notes:

There may be additional options please see full report(s)

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:

The packaging is approved, as provided in the relevant transport rule, to contain liquids of:

| DROP HEIGHT (m) | 1.8 | packing group | density (d) | gross mass (kg) |
|---------------------------|-----|---------------|-------------|-----------------|
| LEAKPROOFNESS (kPa) | 30 | Ī | 1.2 | 276 |
| STACKED AT 3m with RD (d) | 1.2 | П | 1.2 | 276 |
| INTERNAL PRESSURE (kPa) | 270 | III | 1.2 | 276 |

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking.

** To be replaced by the last two digits of the year of manufacture

Revalidation due by: 31/12/ 2027 For further details see www.vca.gov.uk

Sianed:

for Zivad Akhlag. Head of Dangerous Goods VCA DGO