



Vehicle  
Certification  
Agency



Maritime &  
Coastguard  
Agency



Department  
for Transport



VCA Dangerous Goods Office  
Wesley House  
Bull Hill, Leatherhead  
Surrey, KT22 7AH, UK  
T +44 (0)1372 226110  
E dgenquiries@vca.gov.uk  
www.vehicle-certification-agency.gov.uk

# CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number: 6882

**NOT TRANSFERABLE**

Application No.: 9423

Issue number and date: 03 07/12/2023

**Issued to:** RAMSDEN & WHALE LTD  
Harrold Street  
Great Bridge  
Tipton  
West Midlands  
DY4 0JF

Packaging type: 1A2 Description:  
Drum, steel, removable head

Test Contents:  
Tested with sand of density 1.6g/cm3  
and 500 micron particle size and empty  
five litre jerricans to reduce density

Capacity: 210 litres Stainless: No Tinplated: No  
Metal thickness Body: 0.85 mm Base: 0.82 mm Head: 0.93 mm Tare mass: 15.82 kg  
Diameter: 605 mm Height: 875 mm Rolling hoop(s): Yes Full aperture: Yes Head gasket: 10mm sponge rubber  
Closing ring: Lever action clamping ring

No closures in head: 2 Handle: n/a

Steel	Steel
Size: 2"	Size: 3/4"
Type:	Type:
Steel Bung	Steel Bung
Maker:	Maker:
Technocraft	Technocraft
Trisure	Trisure
Overcap: <input type="checkbox"/>	Overcap: <input type="checkbox"/>
Washer/wad and Closure Torque	Washer/wad and Closure Torque
Polyethylene 20 Nm	Polyethylene 15 Nm
Nm	Nm

Bungs are optional

For additional options see schedule issue no date.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:	The packaging is approved, as provided in the relevant transport rule, to contain solids of:		
DROP HEIGHT (m)	1.2	packing group	density (d) gross mass (kg)
STACKED AT 3 m with BD (d)	0.97	I	-
		II	0.97 215
		III	0.97 215

**THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT**

Packagings of the sample specifications shall bear the marking:

**U** 1A2/Y215/S/\*\*/GB/6882

\*\* To be replaced by the last  
two digits of the year of  
manufacture

Revalidation due by: 31/12/ 2028

For further details see www.vca.gov.uk

Signed:

for Ziyad Akhlaq, Head of Dangerous Goods VCA DGO